

TECHNICAL SPECIFICATIONS

RETHINK PRODUCTION PRINTING

SYSTEM SPECIFICATIONS

Resolution	2,400 x 3,600 equiv. dpi x 8 bit
Paper weight	52 - 450 g/m ²
Duplex unit	52 - 450 g/m ²
Paper sizes (max.)	13" x 19.2" 13" x 51" simplex 13" x 35.43" duplex
Paper input capacity	14,140 sheets
Paper output capacity	LS-507 Stacker: 6,200 sheets FS-541 Finisher: 3,300 sheets Max. output capacity: 15,700 sheets
Main unit dimensions (W x D x H)	45.3" x 36.7" x 63.8"
Main unit weight	1,235 lb
Power requirements	208 V to 240 V, 48 A - 2 x NEMA L6-30R outlets

PRODUCTIVITY

AccurioPress C14010/S

A4 - max. per minute	140 ppm
A3 - max. per minute	80 ppm
SRA3 - max. per minute	76 ppm
A4 - max. per hour	7,981 pph

AccurioPress C12010/S

A4 - max. per minute	120 ppm
A3 - max. per minute	69 ppm
SRA3 - max. per minute	65 ppm
A4 - max. per hour	6,832 pph

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.